

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number  
**WO 2005/085008 A1**

(51) International Patent Classification<sup>7</sup>: **B60R 19/00,**  
E01F 15/14

(74) Agent: **FÖRSVARETS MATERIELVERK;** Patent-  
heten, S-115 88 Stockholm (SE).

(21) International Application Number:  
PCT/SE2005/000323

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

(22) International Filing Date: 4 March 2005 (04.03.2005)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:  
0400535-1 4 March 2004 (04.03.2004) SE

(71) Applicant (for all designated States except US):  
**VÄGVERKET [SE/SE];** Vägverket Produktion, S-781 87  
Borlänge (SE).


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **CARSSON, Arne**  
[SE/SE]; Sälgvägen 4, S-660 50 Vålberg (SE).

[Continued on next page]

(54) Title: **IMPACT ATTENUATOR FOR VEHICLE AND METHOD**



(57) Abstract: The invention relates to an impact attenuator, which is arranged flexible longitudinally as well as sideways (as a trailer). The impact attenuator (1) comprises a rear part (2) with two wheels (22), an attenuating part (3) and a front part (4) with two pivot wheels (41) and a coupling part (5) for connection to the vehicle (6). The coupling part (5) comprises a damper (51) for dampening part of the force during a collision against the impact attenuator (1). During a minor collision against the impact attenuator the collision force is mainly absorbed by the damper (51). The damper (51) regains after a collision its original position and the impact attenuator can remain operative. During a larger collision against the impact attenuator the collision forces is absorbed also by the attenuating part (3).

BEST AVAILABLE COPY

WO 2005/085008 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— with international search report